# Meet, in a New Fashion

· **3 Colour Options[1]: Creativity Joins Productivity**

Ivory White  |  Sandy Gold  |  Stella Turquoise

· **48MP Camera: Inescapable Clarity**

Auto Zoom in on the speaker[2]  |  Higher SNR[3]

· **Voice Localisation[4] via 6-element Mic Array**

Auto Gain  |  Noise Cancellation  |  Anti-reverberation

· **Seam Speakers[5], Creative Acoustic Structure**

2.1 Stereo Sound  |  40W Powerful Speakers

· **Type-C[6] Connector, Bridging the Divide**

Carrying Video & Audio & Touch Signals
Accessing the Wide-angled Camera and Powerful Mic Array

---

1. Only the lower bezel of MAXHUB V5 Vogues series have those colour options.
2. MAXHUB V5 may zoom in on the speaker automatically during a meeting. The camera would locate the speaker via pattern recognition and voice localisation algorithms.
3. SNR refers to the Signal-to-Noise Ratio of the imaging system. The 48MP Camera of MAXHUB V5 Vogue Series achieves higher SNR during a UHD or FHD teleconference by gathering more light information and reducing the electric noise in the imaging process.

4. Voice localisation locates the direction speaker with the microphone array and guides the camera for auto zoom in on the speaker.
5. Seam speakers refer to the two front-facing speakers at the lower bezel of MAXHUB V5 featuring narrow openings.
6. A MAXHUB V5 Vogue Series includes 2 USB Type-C ports. By connecting to a laptop, it projects the laptop's screen onto and plays sound from the MAXHUB V5 with reverse touch control. Meanwhile, the laptop may access the built-in camera and microphone array as alternative video and audio signal input.

| Specification | V65FA | V75FA |
|---|---|---|
| **Display** | | |
| Size | 65 inch | 75 inch |
| Ratio | 16:9 | 16:9 |
| Resolution | 3840×2160 | 3840×2160 |
| Contrast Ratio | 1200:1 | 1200:1 |
| Viewing Angle | 178° (H/V) | 178° (H/V) |
| Colour Gamut | 90% NTSC | 90% NTSC |
| Backlight Structure | DLED | DLED |
| Lifespan | ≥30,000 hours | ≥30,000 hours |
| **Touch System** | | |
| Touch Principle | Infrared | Infrared |
| Touch Points | 20 Points | 20 Points |
| Supported Systems | Windows 10/Windows 8/ Windows 7/Windows XP/ Android/Linux/macOS X/Chrome | Windows 10/Windows 8/ Windows 7/Windows XP/ Android/Linux/macOS X/Chrome |
| Minimum Recognisable Object | 2mm | 2mm |
| Touch Object | Finger, Stylus | Finger, Stylus |
| Touch Accuracy | ±1mm | ±1mm |
| Writing Height | ≤2mm | ≤2mm |
| Touch Resolution | 32768(W)×32768(D) | 32768(W)×32768(D) |
| **Speakers** | | |
| Channel | 2.1 | 2.1 |
| Power | 2×10W+20W | 2×10W+20W |
| **Microphone** | | |
| Quantity | 6 | 6 |
| Voice Pickup Range | Up to 8m | Up to 8m |
| **Camera** | | |
| Quantity | 1 | 1 |
| Pixels | 48MP | 48MP |
| Location | In the Middle of the Upper Bezel | In the Middle of the Upper Bezel |
| **I/O Ports** | | |
| HDMI IN | 1 | 1 |
| USB 2.0 | 1 | 1 |
| USB 3.0 | 2 | 2 |
| USB Type-C | 2 | 2 |
| TOUCH | 1 | 1 |
| AUDIO OUT | 1 | 1 |
| RS232 | 1 | 1 |
| **Compatible Modules*** | | |
| PC Module | MT51 (Windows 10) | MT51 (Windows 10) |
| Android Module | SA08 (Android 9.0) | SA08 (Android 9.0) |
| **Accessories** | | |
| Power Cable | ×1 | ×1 |
| Stylus | ×2 | ×2 |
| Wall Mount | ×1 | ×1 |
| Wi-Fi Module | ×1 | ×1 |
| **Environment** | | |
| Operation Temperature | 0°C to 40°C | 0°C to 40°C |
| Operation Humidity | 10% to 90%RH | 10% to 90%RH |
| Storage Temperature | -20°C to 60°C | -20°C to 60°C |
| Storage Humidity | 10% to 90%RH | 10% to 90%RH |
| Altitude | ≤5000 metres | ≤5000 metres |

Compatible Modules*: Sold separately.